



# GT-64

GSM / GPRS MODEM TERMINAL

powered by GE864-PY



Dual SIM Card selectable via AT Command

The GT-64 is a Quad Band GSM/GPRS Modem Terminal.

## Features:

- Quad-Band 850/900/1800/1900
- Data, SMS, Voice & Fax
- GPRS class 10
- Embedded TCP/IP stack
- Power Supply : 10.8 - 31.2 VDC or USB
- Serial Interface : RS232 or USB
- Audio Interface : 6 pin Micro-Fit
- RF Connector : SMA Female
- Size: 85 x 54 x 23mm




# GT-64

GSM / GPRS MODEM TERMINAL

powered by GE864-PY



RS232	PWR	AUX
1 = DCD	1 = 10.8 - 31.2 Vdc	1 = MIC_N
2 = RX	2 = GND	2 = SPK_N
3 = TX	<b>USB</b>  1 = V BUS (+ 5V)	* 3 = OUT_N (Emitter from Photo Transistor)
4 = DTR		4 = MIC_P
5 = GND		5 = SPK_P
6 = DSR		* 6 = OUT_P (Collector from Photo Transistor)
7 = RTS		
8 = CTS		
9 = N/C		
10 = GND	5 = Ground	

\* Please Note: Pins 3 and 6 can also be configured as 2 I/O Lines, in stead of the optically isolated output.

# GT-64

GSM / GPRS MODEM TERMINAL

powered by GE864-PY



## Optional Accessories:



Taoglas TG.22  
*GSM Antenna*



Microfit to AUX /  
Audio Cable *KA13GT*



Power Supply  
*PS100*



Microfit to RS-232 DB9 Female Cable  
*KA01MFT*



USB to mini USB cable  
*GT-USB*