

SARA-G3 series

GSM/GPRS modules

Standard Professional Automotive

CELLULAR

Highlights

- GSM/GPRS functionality scalable to customer needs
- Seamless drop-in migration from SARA-U UMTS/HSPA modules
- Smallest footprint; lowest standby current: < 0.90 mA
- Extended temperature range: -40 to +85°C
- Simple integration of u-blox GNSS and A-GNSS
- CellLocate®: location based on cellular network
- Manufactured in ISO/TS 16949 certified production sites



SARA-G3 series:
16.0 x 26.0 x 2.4* mm

Product description

The SARA-G3 series of GSM/GPRS modules feature extremely low power consumption and a miniature LGA form factor. SARA-G3 modules are interchangeable, and have been designed with the diverse needs of M2M customers in mind. Different functionalities and feature sets are available to meet different customer and application requirements.

SARA-G340/G350 are full-feature GSM/GPRS modules with a comprehensive feature set, including an extensive set of internet protocols (TCP, UDP, HTTP, FTP and SMTP). They have fully integrated access to u-blox GNSS positioning chips and modules, along with embedded A-GNSS (AssistNow Online and AssistNow Offline) functionality. SARA-G350 is the quad-band version for global connectivity and SARA-G340 (900/1800 MHz) is the dual-band version for cost optimized use in Europe and Asia. Their rich feature set enables customers to easily develop a wide range of M2M devices with minimum software development on the host processor.

SARA-G300/G310 modules target high volume, cost sensitive applications, and provide “bit pipe” GSM/GPRS functionalities while minimizing the customer’s total cost of ownership. Functionalities requiring dedicated and expensive hardware components are eliminated where they are not needed or can be implemented in the host processor.

The SARA-G350 ATEX is an ATEX / IECEx certified variant that further complements the product family by offering the ideal solution for the development of smart devices deployed in potentially explosive environments.

u-blox cellular modules are certified and approved by the main regulatory bodies and operators. RIL software for Android and Embedded Windows are available free of charge. SARA-G3 modules are manufactured in ISO/TS 16949 certified sites. Each module is tested and inspected during production. The modules are qualified according to ISO 16750 – Environmental conditions and electrical testing for electrical and electronic equipment for road vehicles.

Product selector

Model	Bands	Positioning	Interfaces	Audio	Features	Grade
	GSM/GPRS quad-band GSM/GPRS dual-band (900/1800 MHz)	GNSS via Modem AssistNow Software CellLocate®	UART GPIO DDC for u-blox GNSS	Analog Audio Digital Audio	Network indication Antenna Supervisor Jamming Detection Embedded TCP/UDP Embedded FTP, HTTP, SMTP Embedded SSL Dual stack IPv4/IPv6 FW update via serial interface eCall / ERA-GLONASS Low power idle-mode ATEX certification	Standard Professional Automotive
SARA-G300	•		2		•	Standard
SARA-G310	•		2		•	Standard
SARA-G340	•	• • •	2 4 1	• •	• • • • • • • • • •	Professional
SARA-G350	•	• • •	2 4 1	• •	• • • • • • • • • •	Professional Automotive
SARA-G350 ATEX	•	• • •	2 4 1	• •	• • • • • • • • • •	Professional Automotive

* Module height is 2.4 mm from version 02 onwards (3 mm in version 01)

Features

GSM	GSM 850/900/1800/1900 MHz ¹ GSM 900 /1800 MHz ² 3GPP Release 99
GPRS	GPRS Class 10, CS1-CS4 - up to 85.6 kb/s PBCCH support
CSD	GSM max 9.6 kb/s
AT Commands	3GPP 27.005, 3GPP 27.007 u-blox AT command extension 3GPP 27.010 MUX protocol
SMS	MT/MO Text/PDU mode
Firmware upgrade	Via UART
SARA-G340/G350 only:	
Voice	HR / FR / EFR / AMR Echo cancellation Noise reduction
Protocols	Embedded TCP/IP, UDP/IP, HTTP/FTP, SSL and TLS 1.2 support
Network	Jamming detection
GNSS Interfaces	Direct access to u-blox GNSS via module AssistNow software for faster acquisition CellLocate® & Hybrid Positioning
Special features	In-band modem Bearer Independent Protocol (BIP) IPv6 support over PPP eCall and ERA-GLONASS support

¹ SARA-G310/G350

² SARA-G300/G340

Electrical data

Power supply	3.00 to 4.50 V (extended)	
Power consumption	Power Off:	< 40 µA
	Idle mode ⁴ :	< 0.9 mA
	Idle mode ⁵ :	< 5.0 mA
	Connected:	< 250 mA

⁴ SARA-G300 and SARA-G310: requires external 32 kHz signal

⁵ SARA-G300 and SARA-G310: without external 32 kHz signal

Interfaces

Common to all modules:	
Antenna	50 Ω SMT pad
Serial Port	1 UART for data and AT commands 1 UART for AT commands, tracing, and FW update
SIM	1.8V and 3V
SARA-G340/G350 only:	
GPIO	4, controllable over AT commands
GNSS serial	1 DDC (I2C)
Audio	1 analog 1 digital (I2S/PCM)

Legal Notice

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.

Copyright © 2016, u-blox AG

Package

96 pin LGA: 16.0 x 26.0 x 2.4* mm, < 3 g

* Module height is 2.4 mm from version 02 onwards (3 mm in version 01)

Environmental data, quality & reliability

Operating temperature -40 to +85°C (extended range)

RoHS compliant (lead-free)

Qualification according to ISO 16750

Manufactured in ISO/TS 16949 certified production sites

ATEX / IECEx certification (SARA-G350 ATEX)

Certifications and approvals

SARA modules offer a comprehensive set of regulatory certifications and approvals, including R&TTE, GCF, PTCRB, FCC, IC, NCC, ICASA, and Anatel. Contact your closest u-blox representative for latest approvals.

Support products

EVK-G35	Evaluation Kit for SARA-G340/G350
EVK-G31	Evaluation Kit for SARA-G300/G310
RIL software	Android 2.3 and 4.x Embedded Windows 6.x 7.x

Product variants

SARA-G300	Cost optimized dual-band (900/1800 MHz) GSM/GPRS data module
SARA-G310	Cost optimized quad-band GSM/GPRS data module
SARA-G340	Dual-band (900/1800 MHz) GSM/GPRS module, extended feature set
SARA-G350	Quad-band GSM/GPRS module, extended feature set
SARA-G350 ATEX	Quad-band GSM/GPRS module, ATEX/IECEx certified

Further information

For contact information, see www.u-blox.com/contact-us.

For more product details and ordering information, see the product data sheet.